

<b>ZTE SMXA/5 Board Datasheet</b>	
Performance	128 Gbps
Vadid Slot	ZXA10 C320 slot 3/4.
Interface	<ul style="list-style-type: none"> <li>• ZXA10 C320 switching and control card</li> <li>• 1 out-of-band NM interface</li> <li>• 1 serial interfac</li> <li>• 1 monitor interface</li> <li>• 1 GE uplink electrical interface</li> <li>• SMXA with daughter card</li> </ul> <p>The GE optical interface is available when a UCDC/1 daughter card is installed.</p> <p>The GE optical interface can be modified to a 10GE optical interface with a UCDC/3 daughter-card is installed.</p> <p>1 GE optical interface and 1 10GE optical interface are available when a UCDC/5 daughter card is installed.</p>
Function	<p>ZXA10 C320 SMXA uplink daughter card: UCDC/5</p> <ul style="list-style-type: none"> <li>• Supports two GE SFP interfaces and 1-port GE SFP interface.</li> <li>• Supports 1588v2, and clock/time synchronization.</li> <li>• Supports Ethernet uplink.</li> </ul>
Power Consumption (W)	27 W (static), 36 W (maximum), 32 W (typical)
Dimensions	200.25 mm × 37 mm × 225 mm (Height × Width × Depth)
Weight	1.031 kg